



Delivery control



Quick snap with ball valve and pressure gauge unit with manometer



Ball valve with mouth piece

Description

Spiral pump SP-Y is of multiple use and features high power combined with compact design. With the delivery control the pump can be controlled continuously from standstill to maximum speed. As an option the delivery control can be fixed with an extension cord directly at the end of the material hose so that the operator can react immediately to avoid that the material gets under pressure.

Technical data

Supply	230 V
Motor power	1.8 kW
Working pressure	max. 15 bar
Delivery-ininitely variable	0 - 13.5 l/min
Grain size-material	max. 3 mm
Filling height	95 cm
Weight	22 kg
Height/width/length-working position	(cm) 95/45/90
Height/width/length-transport	(cm) 55/40/70

Delivery range

moving device, 30 litre plastic material container, splash guard, rotor*, stator*, infinitely variable delivery control, 5 m material hose Ø 13 mm with lock-type Geka coupling, pressure gauge unit with manometer 0 - 40 bar, ball valve R $\frac{1}{2}$ " and quick snap, ball valve with external thread R $\frac{1}{2}$ " and mouth piece

Advantages

- Big material passages - high flow rate
- Cone-shaped material container - self-emptying

Material to be used

- Injection mortar, grain size ≤ 0.3 mm
- Cement paste
- Cement suspension
- Aqueous solution, e.g. micro emulsion
- Machine usable jointing mortar
- Sealing slurries
- Fine filler
- Thick coating, bitumen

*Spare parts: rotor (13563-011), stator (13563-012)

DESOI GmbH

Gewerbestraße 16
36148 Kalbach/Rhön

Phone: +49 6655 9636-0
Fax: +49 6655 9636-6666

E-mail: info@desoi.de
Internet: www.desoi.de

As at 10/10
Errors excepted. Subject to technical modifications.
We are not liable for errata.