

# Pneum. Double Membrane Pump



Pressure reducer with manometer



Quick snap with ball valve



Ball valve with mouth piece

## Double Membrane Pump L-1

Order number: 10688

The compact pneumatic double membrane pump L-1 is suitable for works with high demand on the flow rate in the low pressure range. The delivery pressure is set by the pressure reducer.

### Technical data

Working pressure – infinitely variable	1 – 8 bar
Delivery	max. 21 l/min
Grain size – material	max. 0.5 mm
Pressure ratio	1 : 1
Air pressure	max. 8 bar
Compressor output – required	min. 120 l/min
Weight	10 kg
Height / width / length – working position	(cm) 30 / 30 / 36

### Delivery range

L-1: 5 m material hose Ø 13 mm with ball valve R ½" and quick snap, ball valve with external thread R ½" and mouth piece, suction system, pressure reducer

### Advantages

- Big material passages – high flow rate
- Compact design
- Exact pressure adjustment
- Easy operation and cleaning

### Material to be used

- Injection mortar – grain size ≤ 0.5 mm
- Cement paste
- Cement suspension
- Aqueous solution, e.g. micro emulsion
- Wood preservative



### DESOL GmbH

Gewerbestraße 16  
D-36148 Kalbach/Rhön

Phone: +49 6655 9636-0  
Fax: +49 6655 9636-6666

E-Mail: [info@desoi.de](mailto:info@desoi.de)  
Internet: [www.desoi.de](http://www.desoi.de)